

Model	Equivalent	Car suggestion	Height (mm)	Diameter (mm)	Wire thickness (mm)	Diam (in)	Wt (in)	relative spring rate k
Spidan 56831			328	138	11	5.433	0.433	149.54
Suplex 03207		1.4i+oss	337	138	11	5.433	0.433	149.54
Spidan 56830	RH3243		338	141	11.25	5.551	0.443	153.39
TRW JCS880	RH3243		342	139	11.15	5.472	0.439	154.49
Sachs 997853		no OSS	342	139	11.15	5.472	0.439	154.49
QH56763RMP	RH3243, Sp56831	1.4i+oss	337	138	11.1	5.433	0.437	155.06
Sachs 998404		with OSS	337	138	11.1	5.433	0.437	155.06
Suplex 03206		1.4tdi+OSS	342	139	11.25	5.472	0.443	160.10
Suplex 03171		1.4i	342	139	11.25	5.472	0.443	160.10
QH39742RMP	RH1665, Sp49527	1.4i	342	139	11.25	5.472	0.443	160.10
Spidan 49527			330	138	11.25	5.433	0.443	163.61
KYB RH3243			334	138	11.25	5.433	0.443	163.61
KYB RH3242		1.4i	334	138	11.25	5.433	0.443	163.61
Kilen 022736		1.6	350	136	11.25	5.354	0.443	170.93
Kilen 007264		1.4tdi	350	136	11.25	5.354	0.443	170.93
Suplex 03170	Spidan 49515	1.4tdi	338	137	11.5	5.394	0.453	182.58
Spidan 49515			338	137	11.5	5.394	0.453	182.58
KYB RH1664		1.4tdi / 1.6	330	140	12	5.512	0.472	202.85